



Size

DIMENSIONS
7.25 in x 48 in

THICKNESS
3 mm

Product Specifications

BEVEL
Micro Bevel

WEAR LAYER
28 mil (0.7mm)

FINISH
Aluminum Oxide

INSTALLATION
Glue Down

CONSTRUCTION
Dry Back

SUITABLE LOCATION
On, Above, or Below Grade

SURFACE TEXTURE
Embossed in Register

Warranty

WARRANTY
Lifetime Residential / 30 Year Commercial

CERTIFICATIONS
FloorScore Certified

RADIANT HEAT
Approved

Packaging

SF / CARTON
39.52 sq.ft / carton

EACHES / CARTON
16 planks / carton

CARTONS / PALLET
50 cartons / pallet

PALLETS / TRUCK
20 pallets / truck

Colours



MEL562-1
Elevate



MEL191028-2
Altitude



MEL2147-8
Highland



MEL2147-6
Sherpa




MEL6147-4
Expedition



MEL6147-5
Trek



MEL13031-101
Horizon



MEL2147-3
Saddle



MEL13031-76
Frost



MEL13031-1
Cedar



MEL13031-75
Ascent



MEL13031-08
Glacier

Product Performance

Test Description

Size
Overall Thickness
Critical Radiant Flux
Smoke Density
Static Coefficient of Friction
Static Load Limit

Test Method

ASTM F2055
ASTM F386
ASTM E648
ASTM E662
ASTM D2047
ASTM F970

Requirements

± 0.40 mm
± 0.13 mm
≥ 0.45
≤ 450
≥ 0.50
≤ 5 mils

Test Results

Pass
Pass
Pass / Class I
Pass
Pass
Meets Guidelines

