


Lakeside Park



Martin & Co.
Floors For Life



Features

- I4F Fold Down Locking System
- Kid & Pet Friendly
- Painted Bevel
- Embossed-in-Register
- Radiant Heat Approved
- Foam Pad
- Waterproof Core



Product Information

Product	Lakeside Park Waterproof Laminate Flooring
Construction	Waterproof
Dimention	12mm x 7.5" x 48"
Product Thickness	12mm (10mm core + 2mm pad)
Abrasion Rating	AC4
Finish	UV Cured
Warranty	Lifetime Residential / 5 Year Commercial

Testing

Classification	Method	Result
Class	ASTM F1700	Class III, Type B - Embossed
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm
STC	ASTM E90-09	70
IIC	ASTM E492-09	73
Dimensional Stability	ASTM F2199	Pass: ≤ 0.02 " per linear foot
Resistant to Chemicals	ASTM F925	Pass: Not affected
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens
Reaction to Fire	EN13501-1	Class B fl-s1
Critical Radiant Flux	ASTM E648	Pass, > 0.45 watts/cm ²
Concentration of Dibutyl Phthalate	ISO 16000	$< 1 \mu\text{g}/\text{m}^3$ after 28 days
Concentration of Diethylhexyl Phthalate	ISO 16000	$< 1 \mu\text{g}/\text{m}^3$ after 28 days
Flexibility	EN435	No Damage

Packaging Information

	Length (mm)	Width (mm)	Thickness (mm)	Sq. ft.	Height (mm)	Volume (m ³)	# of carton per Pallet	Weight (lb.)
Plank	1219	190.5	12					
Plank Carton	1228	208	98	20.03 per carton				
Plank Pallet	1240	990	-	901 per pallet	800	1.15	45	1630